




Arc Recessed wall lighting

Designer: Josep Patsi

Description

Recessed wall lighting IP66 Arc LED 9W 3000K Cement Urban grey 404lm

	Finish	Material
Structure	Cement Urban grey	Concrete Aluminium
Diffuser	Sandblasted	Glass



300x140

IP66 IK10 4

TECHNICAL CHARACTERISTICS

Light source

Light source: LED
 Light source power (W): 9W
 Luminaire total power (W): 9W
 Color temperature: LED warm-white
 3000K
 CRI: 80
 Photobiological risk: RG0
 Real Lumen: 404
 Qty Leds: 26
 Lm/Real W: 45
 Life Time: 50.000h L80B20
 Bin / Grup: WS
 MacAdam steps: 3
 UGR: 19.0
 Luminance C0°65°: 700.7
 Luminance 90°65°: 2385.5

GEAR

Gear included: Yes, electronic
 Voltage / Frequency: 230V/50-60Hz
 Dimming protocol: ON-OFF

Luminaire

Double cable exit: Yes
 Recessed in-ground suitable for pedestrian crossing: No
 Seaside: Yes
 Uv Protection: Yes
 Warranty: 5 Years

Logistics

Energy Efficiency: LED A++
 EAN Code: 8435575319264
 Weight in Kg (packaged): 0.12
 Packing: 365 x 135 x 205
 Masterbox: 4

The photograph may not match the reference exactly. Please read the product description to identify the finish.