

55-1573-14-00

V1



## Step Round Signalling




### Description

Signalling Step Round 3.8W 3000K CRI 80 PHASE CUT White IP20 67lm

	Finish	Material
Structure	White	Aluminium

 IP20 IK10 
  50



57

### TECHNICAL CHARACTERISTICS

#### Light source

Light source: LED LUMENS  
 Light source power (W): 3.8W  
 Luminaire total power (W): 3.8W  
 Color temperature: LED warm-white  
 3000K  
 CRI: 80  
 Photobiological risk: RG1  
 Real Lumen: 67  
 Qty Leds: 1  
 Lm/Real W: 18  
 Life Time: 50.000h L80B20  
 Bin / Grup: 3 steps  
 MacAdam steps: 3  
 UGR: 38.6

#### GEAR

Gear included: Yes, electronic  
 Voltage / Frequency:  
 220-240V/50-60Hz  
 Power Factor: 1.00  
 Dimming protocol: PHASE CUT

#### Luminaire

Warranty: 5 Years

#### Logistics

Energy Efficiency: LED A++  
 EAN Code: 8435381462253  
 Net Weight (Kg): 0.19  
 Weight in Kg (packaged): 0.24  
 Packing: 80 x 80 x 95  
 Masterbox: 50

The photograph may not match the reference exactly. Please read the product description to identify the finish.