

Gea Cob LED Aluminium ø125mm Structure

Designer: LEDS C4




Description







Structure IP65/IP67 Gea Cob LED Aluminium ø125mm Stainless steel AISI316 Aluminium Polished Black IK10

	Finish	Material
Structure	Polished Black	Stainless steel AISI316 Aluminium
Diffuser	Transparent	Glass

ø125



133

 IP65/IP67 IK10
  SPOT 17°
  ±15°
  360°
  8
 

TECHNICAL CHARACTERISTICS

Light source

Light source: LED CREE
 Light source power (W): 9W
 Luminaire total power (W): 10.5W
 Color temperature: LED warm-white 2700K
 CRI: 80
 Photobiological risk: RG1
 Real Lumen: 869
 Qty Leds: 1
 Lm/Real W: 83
 Life Time: 50.000h L80B20
 Bin / Grup: 27H
 MacAdam steps: 2
 UGR: 9.2

GEAR

Gear included: Yes, electronic
 Voltage / Frequency:
 100-240V/50-60Hz
 Power Factor: 0.90
 Dimming protocol: ON-OFF

Luminaire

Temperature on the surface: 40
 Double cable exit: Yes
 Drainage: Yes
 Recessed in-ground suitable for pedestrian crossing: Yes
 Public Areas: 2000 kg
 Seaside: Yes
 Uv Protection: Yes
 Warranty: 5 Years

Logistics

Energy Efficiency: LED A++
 EAN Code: 8435381439958
 Weight in Kg (packaged): 0.14
 Packing: 130 x 130 x 140
 Masterbox: 8

The photograph may not match the reference exactly. Please read the product description to identify the finish.