




Tiny Large Recessed wall lighting

Description

Recessed wall lighting IP66 Tiny Large LED 5.9W 3000K Urban grey 74lm

	Finish	Material
Structure	Urban grey	Aluminium
Diffuser	Sandblasted	Glass

 IP66 IK10
  FLOOD 69°
  16



TECHNICAL CHARACTERISTICS

Light source

Light source: LED BRIDGELUX
 Light source power (W): 5.9W
 Luminaire total power (W): 7.8W
 Color temperature: LED warm-white 3000K
 CRI: 80
 Photobiological risk: RG1
 Real Lumen: 74
 Qty Leds: 39
 Lm/Real W: 9
 Life Time: 50.000h L80B20
 Bin / Grup: 1
 MacAdam steps: 3
 UGR: 21.2
 Luminance C0°65°: 46.8
 Luminance 90°65°: 2863

GEAR

Brand: HEP
 Gear included: Yes, electronic
 Voltage / Frequency: 220-240V/50-60Hz
 Power Factor: 0.50
 Dimming protocol: ON-OFF

Luminaire

Double cable exit: No
 Drainage: No
 Recessed in-ground suitable for pedestrian crossing: No
 Seaside: Yes
 Cable meters included: 2
 Uv Protection: Yes
 Warranty: 5 Years
 Ta max: 50°C

Logistics

Energy Efficiency: LED A++
 EAN Code: 8435575319639
 Weight in Kg (packaged): 0.1
 Packing: 171 x 96 x 48
 Masterbox: 16

The photograph may not match the reference exactly. Please read the product description to identify the finish.