





Max ø58mm Trimless AI13-P4W9S1BBZ5

Leds C4 Team

Recessed uplighting IP66 Max ø58mm Trimless LED 4W 3000K Urban grey 286lm



TECHNICAL FEATURES

IP66 IK10



Power (W) : 4W

Total power consumption of light (W) : 4W

Real lumens : 286

Real lm/W : 72

Correlated Colour Temperature (CCT) : LED warm-white 3000K

Lens / reflector angle : NARROW 9°

UGR : <= 16

Structure material : Aluminium

Structure finish : Urban grey

Diffuser material : Glass

Diffuser finish : Transparent

Equipment necessary but not included :

Voltage / frequency : 12V/Max. 350mA

Useful life : 50.000h L80B20

Max. temperature : 25°C

Warranty : 5 Years

Seaside : Yes

Energy efficiency : LED A++

LUMINOTECHNIC FEATURES

Light source: LED CREE

CRI: 90

MacAdam steps: 3

Photobiological risk: RG2

UGR

UGR crosswise: 10.1

UGR lengthwise: 10.1

UGR	
S=0.250	
Ceiling / cavity	0.7
Walls	0.5
Working Plane	0.2
Room dimensions	X=4H, Y=8H
UGR crosswise	10.1
UGR lengthwise	10.1

VENTILATION FEATURES

Power used: 4W

Service value measurement standard: EN 60879:2019

LOGISTICS

Net weight (kg): 0.37

Packaged weight (kg): 0.48

Packaging: 185mm x 120mm x 65mm



20 Un