

VL70UD

Distributed by

LASER LIGHTING

www.laserlighting.com.au | sales@laserlighting.com.au

- *70 wide x 114 high*
- *Integral driver*
- *Direct/Indirect illumination*
- *Downlight options available to 4/7/10/13W*
- *Emergency Option available*
- *Wire or Rod Suspension (adjustable)*
- *Integral tensioning joiner*
- *Plug and play wiring system*
- *Integral mounting guides (easy install)*
- *Standard Colour White or Black (other colours optional)*
- *12 watts/m, 17 watts/m, 24 watts/m, 32 watts/m or 38 watts/m*
- *Solid PCB (removable and replaceable)*
- *Mitred and Cross Over bends available (90 and 135 degree standard)*
- *3K, 4k CRI80+ (CRI95+ optional)*
- *Reported L70 B10 (10K) > 60,000 hrs*
- *Forecasted L70 83,000 hrs*
- *Ledvision PMMA high impact diffuser*
- *RGBW optional*
- *Manufactured in module lengths up to 4m*
- *Rear Power Entry*
- *All photometric data provided in absolute lumens*
- *Manufactured in South Australia*



VL70UD

*Flexible Strip Used

+ Recommended for Upwards Only

	VOLTAGE	WATTAGE
VL70UD-5+	240V AC	5W/m
VL70UD-12	240V AC	12W/m
VL70UD-17	240V AC	17W/m
VL70UD-24	240V AC	24W/m
VL70UD-32	240V AC	32W/m
VL70UD-38	240V AC	38W/m
VL70UD-RGBW*	240V AC	28.8W/m
UPWARD COMPONENT	240V AC	select as required

Downlight options available to 4/7/10/13W.

VL70UD - SUSPENSION MOUNT

VL70UD-5+ - 3000/4000K (5w+ per metre)	
VL70UD-12 - 3000/4000K (12w per metre)	
VL70UD-17 - 3000/4000K (17w per metre)	
VL70UD-24 - 3000/4000K (24w per metre)	
VL70UD-32 - 3000/4000K (32w per metre)	
VL70UD-38 - 3000/4000K (38w per metre)	
VL70UD-28.8 - Dual RGBW (28.8w per metre)	

VL70 UD PROFILE:

70mm wide x 114 mm high

114mm



70mm

INCLUSIONS :
Solid PCB

DIFFUSER :
Ledvision PMMA
high impact

OPTIONS :
Custom colours
Downlights
Emergency