

STRATEGIC LIGHTING

Asset LED IP66

Twin

210° Rotating Lens



145mm

282mm



ASSET Twin

LED Solid State Lighting



Mounting Clip

Construction

Body	6000 Series Extruded Aluminium
Lens	Advanced High Impact, UV Stabilised Polycarbonate
Optics Components	Frosted Diffuser or 60° Optical Lens
Mounting	Injection Moulded Polymer Components For Durability & Long Life
	Variable Mounting Positions Along Spine
	Stainless Steel Mounting Clips
	Stainless Steel Over-Lock Clip For Vibration & Adverse Weather Conditions
Control Gear	Built-in Matching LED Drivers
	<ul style="list-style-type: none"> • Australian Made, High Thermal Transmission Heat Sink • All Fittings Supplied with Flex & Plug • Emergency Models Available • Microwave Sensor Models Available



465mm /
745mm /
1025mm

Electrical Specifications

Model	Length (L)	LED	Lumens	Voltage (v)	Current (I)	Circuit Power
FPA 05224	465mm	2X24W	5880 lm	240v	0.33A	54W: λ0.98
FPA 08248	745mm	2X48W	11760 lm	240v	0.68A	102W: λ0.98
FPA 11272	1025mm	2X72W	17640 lm	240v	1.00A	150W: λ0.98


Specify When Ordering: • Medium Beam - 60° Lens
• Wide Beam - Diffused Lens

Options


- CCT: Standard 4000K; Optional 3000K, 5000K, 6000K
- DALI Dimmable Options
- Emergency Lighting Pod: C₀=D63 C₉₀=D50
- Microwave Presence Detection & Daylight Harvesting - Combination

Photometry

Asset With 60° Lens



Asset With Diffused Lens



Impact Resistant

IP66 Rated



High Output LED

Energy Efficient