

Metro 600



FEATURES

- Australian designed and manufactured from high-quality materials
- Contemporary design which is stylish, unobtrusive and aesthetically pleasing

ALL MODELS

- 240VAC 50HZ input 198-264VAC and over voltage protection
- Quick-connect push terminal
- Mounting: surface
- Tridonic/VS/Mean Well driver

LUMINAIRE CONSTRUCTION

- Corrosion-resistant aluminium base plate
- Plexiglas opal diffuser that gives soft, even light (matt finish)
- Spring steel clips

OPTIONS:

- Microwave sensor
- Dimmable: DALI/Switch DIM/0-10v
- IPX4 rating
- Fused terminal block


SUGGESTED APPLICATIONS

- Cafes
- Childcare centres
- Foyers
- Kitchens
- Living areas
- Nursing homes/Aged care
- Office spaces
- Restaurants
- Schools
- Walkways and stairwells
- Clubs

80mm



Ø600mm



Model	Light Source/Lamp	Lumen Luminaire (lm) 3000°K	Lumen Luminaire (lm) 4000°K	Lumen Luminaire (lm) 5000°K	Power Lamp (W)	Power Luminaire (W)	Colour Rendering Index (CRI)	Power Factor	LED Qty	LED Type	LED Brand	IP Rating	Dimensions (mm)		Weight (kg)
													Ø	H	
MR600LED30W-XXX	LED	2922	3059	3219	30	34	>80	0.93	36	SMD	Nichia	IP20	600	80	2.17
MR600LED35W-XXX	LED	3409	3569	3756	35	39	>80	0.95	36	SMD	Nichia	IP20	600	80	2.17
MR600LED46W-XXX	LED	4481	4691	4936	46	51	>80	0.97	36	SMD	Nichia	IP20	600	80	2.17
MR600LED65W-XXX	LED	6332	6628	6975	65	70	>80	0.97	36	SMD	Nichia	IP20	600	80	2.17

NOTE: XXX denotes CRI and colour temperature. E.g.: CRI 80 and 3000°K = 830.
*Correctable to 0.9 (HPF Model)

MADE IN AUSTRALIA



10 year consumer warranty (housing). 5 year warranty (electrical). Refer to warranty card for more information. Due to continual improvement through research and development, EL-Electric reserves the right to change specifications without notice. Must be installed by a Licenced Electrician.