

Multidir Evo Recessed

Designed by LedsC4 Architectural



+
Multidir Evo
Recessed

INDOOR

Ceiling P. 316



Multidir Evo Recessed comes with a single and double lens in different finishes and with Trimy trimless options. Its new-and-improved Cardan system is an ideal choice for retail settings, both the LED and GU10 versions.

Multidir Evo Recessed est proposé avec une optique simple et double dans différentes finitions et avec des options Trimy sans collerette. Son système de cardan remanié et amélioré constitue un choix idéal pour les espaces de commerce de détail, tant en version LED que GU10.

DOWNLIGHTS










Multidir Evo

BODY MAT	DIF MAT	50000h	2
AL	PC	L80 B20	MacAdam

Multidir Evo Multidir Small Single Downlight

IP		
54	40°	40°








Code exemple / Exemple d'élaboration d'une référence: **AU11-P8V9S3OS60**

Model	W	K / CRI / Real lm	Optics	Source	Finishes
AU11 - Single / recessed / trim Monopoint / encastré / avec cadre 0-20 mm 110x110 IP54  	 P8 7.6W	V9 2700K / CRI90 / 863 lm	S3 17°	OS ON-OFF 220-240V	 60 14 34
		W9 3000K / CRI90 / 860 lm	M3 24°	DS DALI-2 110-277V	
		X9 4000K / CRI90 / 854 lm	F1 64°	BB 30V/max.250mA	
AU12 - Single / Recessed / Trimless Monopoint / Encastré / Sans Cadre 0-20 mm 100x100 IP54  	 11 11.7W	V9 2700K / CRI90 / 1087 lm	S3 18°	OU ON-OFF 100-240V	
		W9 3000K / CRI90 / 1144 lm	M3 25°	DS DALI-2 110-277V	
		X9 4000K / CRI90 / 1141 lm	F1 64°	XB CASAMBI 220-240V	
	AA GU10	G1	NA	BU 100-240V	

Multidir Evo Multidir Small Double Downlight

IP		
54	40°	40°

Code exemple / Exemple d'élaboration d'une référence: **AU13-P8V9S3OS60**

Model	W	K / CRI / Real lm	Optics	Source	Finishes
AU13 - Twin / recessed / trim Bipoint / encastré / avec cadre 0-20 mm 208x110 IP54  	 P8 2 x 7.6W	V9 2700K / CRI90 / 1739 lm	S3 17°	OS ON-OFF 220-240V	 60 14 34
		W9 3000K / CRI90 / 1721 lm	M3 24°	DS DALI-2 110-277V	
		X9 4000K / CRI90 / 1708 lm	F1 64°	BB 30V/max.250mA	
AU14 - Twin / Recessed / Trimless Bipoint / Encastré / Sans Cadre 0-20 mm 200x100 IP54  	 11 2 x 11.7W	V9 2700K / CRI90 / 2288 lm	S3 18°	OU ON-OFF 100-240V	
		W9 3000K / CRI90 / 2282 lm	M3 25°	DS DALI-2 110-277V	
		X9 4000K / CRI90 / 2282 lm	F1 64°	XB CASAMBI 220-240V	
	AA 2 x GU10	G1	NA	BU 100-240V	

Multidir Evo

Multidir Big Single Downlight





Code exemple / Exemple d'élaboration d'une référence: **AU17-18V9S3OU60**

Model	W	K / CRI / Real lm	Optics	Source	Finishes
AU17 - Single / Recessed / Trim Monopoint / Encastré / Avec Cadre 0-20 mm 160×160 <div style="display: flex; align-items: center; margin-top: 10px;"> </div>	18 18.2W	V9 2700K / CRI90 / 1993 lm	S3 15°	OU ON-OFF 100-240V	60 14 34
		W9 3000K / CRI90 / 1971 lm	M3 23°	DS DALI-2 110-277V	
		X9 4000K / CRI90 / 2011 lm	F1 63°	XB CASAMBI 220-240V BB 33V/ max.500mA	
AU18 - Single / Recessed / Trimless Monopoint / Encastré / Sans Cadre 0-20 mm 150×150 <div style="display: flex; align-items: center; margin-top: 10px;"> </div>	25 25.4W	V9 2700K / CRI90 / 2715 lm	S3 14°	OU ON-OFF 100-240V	
		W9 3000K / CRI90 / 2735 lm	M3 23°	DS DALI-2 110-277V	
		X9 4000K / CRI90 / 2696 lm	F1 63°	XB CASAMBI 220-240V BB 33V/max.700mA	
	33 33.3W	V9 2700K / CRI90 / 3409 lm	S3 14°	OS ON-OFF 220-240V	
		W9 3000K / CRI90 / 3439 lm	M3 23°	DS DALI-2 110-277V	
		X9 4000K / CRI90 / 3375 lm	F1 63°	XB CASAMBI 220-240V BB 33V/ max.900mA	
39 37.5W	V9 2700K / CRI90 / 3891 lm	S3 15°	OU ON-OFF 100-240V		
	W9 3000K / CRI90 / 3968 lm	M3 23°	DS DALI-2/PUSH 220-240V		
	X9 4000K / CRI90 / 3878 lm	F1 63°	XB CASAMBI 220-240V BB 33V/ max.1050mA		
AA GU10	G1	NA	BU 100-240V		

Multidir Evo
Multidir Big Double Downlight

IP		
54		40°

Code exemple / Exemple d'élaboration d'une référence: **AU19-18V9S30U60**







Model	W	K / CRI / Real lm	Optics	Source	Finishes
AU19 - Twin / recessed / trim Bipoint / encastré / avec cadre 0-20 mm 310x160  	18 2 x 18,2W	V9 2700K / CRI90 / 4017 lm	S3 15°	OU ON-OFF 100-240V	60 14 34
		W9 3000K / CRI90 / 3943 lm	M3 23°	DS DALI-2 110-277V	
		X9 4000K / CRI90 / 4022 lm	F1 63°	XB CASAMBI 220-240V BB 33V/max.500mA	
AU21 - Twin / Recessed / Trimless Bipoint / Encastré / Sans Cadre 0-20 mm 305x150  	25 2 x 25.4W	V9 2700K / CRI90 / 5469 lm	S3 14°	OU ON-OFF 100-240V	
		W9 3000K / CRI90 / 5470 lm	M3 23°	DS DALI-2 110-277V	
		X9 4000K / CRI90 / 5391 lm	F1 63°	XB CASAMBI 220-240V BB 33V/max.700mA	
	33 2 x 33.3W	V9 2700K / CRI90 / 6867 lm	S3 14°	OS ON-OFF 220-240V	
		W9 3000K / CRI90 / 6877 lm	M3 23°	DS DALI-2 110-277V	
X9 4000K / CRI90 / 6750 lm		F1 63°	XB CASAMBI 220-240V BB 33V/max.900mA		
39 2 x 37.5W	V9 2700K / CRI90 / 7838 lm	S3 15°	OU ON-OFF 100-240V		
	W9 3000K / CRI90 / 7936 lm	M3 23°	DS DALI-2/PUSH 220-240V		
	X9 4000K / CRI90 / 7756 lm	F1 63°	XB CASAMBI 220-240V BB 33V/ max.1050mA		
AA 2 x GU10	G1	NA	BU 100-240V		

Multidir Evo Big Single Downlight 33W Multidir Evo Big Single Downlight 25W Multidir Evo Big Single Downlight 18W Multidir Evo Small Double Downlight GU10



Drivers
Drivers

P. 1000

	ON-OFF IP20	71-3542-00-00	71-6653-00-00	71-6142-00-00	-
	PHASE CUT 240V IP20	-	71-A299-00-00	71-4898-00-00	-
	1-10V PUSH IP20	71-4708-00-00	71-4708-00-00	71-7710-00-00	-
	DALI2 IP20	-	-	71-B407-00-00	-
	DALI2 PUSH IP20	71-A303-00-00	71-A192-00-00	-	-
	CASAMBI IP20	71-A260-00-00	71-A260-00-00	71-A260-00-00	-

Lens accessories
Accessoires optiques



Honeycomb panel (5u.)
Grille en nid d'abeille (5 u.)

71-A855-60-00 71-A855-60-00 71-A855-60-00 71-A854-60-00