


Ceiling rose surface-mounted/ built-in  
Monture surface/ encastré



Remote installation with mini built-in ceiling rose  
Installation à distance avec monture mini encastré

### Tubs Modular Track With 5 Spheres



10-50 mm

87 × 244 mm (00-A116)  
108 × 314 mm (00-A117)

18 mm


BODY MAT	DIF MAT		50000h	3	
AL	PMMA		L80 B20	MacAdam	

LED | K 3000 | CRI 90 | W Total 26.5 | Real Lm 320

● 05 Black Noir  
○ M1 Opal white Blanc opale

		Structure	Difussor	Code
	ON-OFF 220-240V	05 ●	M1 ○	00-A116-05-M1
	DALI 100-240V	05 ●	M1 ○	00-A117-05-M1
	ON-OFF 100-240V	05 ●	M1 ○	00-A118-05-M1
	DALI 100-240V	05 ●	M1 ○	00-A119-05-M1

### Tubs Modular Lineal & track With 3 Pendants with Honeycomb



10-50 mm

87 × 244 mm (00-A104)  
108 × 314 mm (00-A105)

18 mm

BODY MAT	DIF MAT		50000h	3	
AL	PMMA		L80 B20	MacAdam	

LED | K 3000 | CRI 90 | W Total 37.5 | Real Lm 1696

● 05 Black Noir  
○ M1 Opal white Blanc opale

		Structure	Difussor	Code
	ON-OFF 220-240V	05 ●	M1 ○	00-A104-05-M1
	DALI 100-240V	05 ●	M1 ○	00-A105-05-M1
	ON-OFF 100-240V	05 ●	M1 ○	00-A106-05-M1
	DALI 100-240V	05 ●	M1 ○	00-A107-05-M1

1.5 mm<sup>2</sup>      2.5 mm<sup>2</sup>

<b>105W</b>	15 m	25 m
<b>150W</b>	10 m	18 m
<b>180W</b>	8 m	15 m
<b>240W</b>	5 m	13 m
<b>270W</b>	5 m	8 m

Maximum distance between the mini recessed canopy and the equipment depending on the section of the cable.

Distance maximale entre la mini verrière encastrée et l'équipement en fonction de la section du câble.

